

**LANKA WALLTILES PLC**

215, Nawala Road, Narahenpita, Colombo 05, Sri Lanka.Tel:  
+94-11-2808050 Fax: +94-11-2806232  
Email: [info@lankatiles.com](mailto:info@lankatiles.com) Website: [www.lankatiles.com](http://www.lankatiles.com)  
Factory: Meepe, Padukka. Tel: 0117309804-9  
Fax:0112859168  
Co. Reg. No. PQ55



**TECHNICAL SPECIFICATION**



Glazed Porcelain Floor Tiles produced by LANKA WALLTILES PLC comply with ISO 13006:2018(E) Annex H, BS EN 14411:2012 Annex H, Specifications and SLS 1181:2019 standards.

**SKU : FAZ-PLA---M0942B5**

**Series : Plasco**

**Size: 1000x1000mm**

**Surface: Satin Matt**

| DIMENSIONS & SURFACE QUALITY                              | IMAGE                                                                               | Test methods<br>BS EN ISO                                                                                                                                                                                              | GLAZE PORCELAIN<br>Annex H<br>Group<br>B I b                                                                           | TEST<br>STATUS |
|-----------------------------------------------------------|-------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------|----------------|
| Length & width                                            |    | ISO 10545-2                                                                                                                                                                                                            | +/-0.3%                                                                                                                | Comply         |
| Thickness                                                 |    | ISO 10545-2                                                                                                                                                                                                            | +/-5.0%                                                                                                                |                |
| Straightness of sides                                     |    | ISO 10545-2                                                                                                                                                                                                            | +/-0.3%                                                                                                                |                |
| Centre curvature                                          |    | ISO 10545-2                                                                                                                                                                                                            | +/-0.4%                                                                                                                |                |
| Edge curvature                                            |    | ISO 10545-2                                                                                                                                                                                                            | +/-0.4%                                                                                                                |                |
| Warpage                                                   |    | ISO 10545-2                                                                                                                                                                                                            | +/-0.4%                                                                                                                |                |
| Rectangularity                                            |   | ISO 10545-2                                                                                                                                                                                                            | +/-0.3%                                                                                                                |                |
| Surface quality                                           |  | ISO 10545-2                                                                                                                                                                                                            | Minimum of 95 % of tiles shall be free from visible defects that would impair the appearance of a major area of tiles. |                |
| PHYSICAL PROPERTIES                                       |                                                                                     |                                                                                                                                                                                                                        |                                                                                                                        |                |
| Water absorption                                          |  | ISO 10545-3                                                                                                                                                                                                            | 0.5 % < E ≤ 3 %<br>Individual Max 3.3%                                                                                 | Comply         |
| Breaking strength                                         |  | ISO 10545-4                                                                                                                                                                                                            | Not less than 1100 N<br>(Thickness ≥ 7.5mm)                                                                            |                |
| Modulus of rupture                                        |  | ISO 10545-4                                                                                                                                                                                                            | Min 30 N/ mm <sup>2</sup><br>Individual min 27 N/mm <sup>2</sup>                                                       |                |
| Resistance to surface abrasion-glazed tiles               |  | ISO 10545-7                                                                                                                                                                                                            | Reported abrasion class and cycle passed                                                                               | Class 2        |
| Resistance to Slip                                        |  | BS 7976 / EN 16165                                                                                                                                                                                                     | Reported Slippery class                                                                                                | P2             |
| Scratch Resistance (Mohs Hardness Scale)                  |  | NA                                                                                                                                                                                                                     | Not Specified                                                                                                          | 6              |
| Resistance to Thermal shock                               |  | ISO 10545-9                                                                                                                                                                                                            | Required                                                                                                               | Comply         |
| Resistance to crazing-glazed tiles                        |  | ISO 10545-11                                                                                                                                                                                                           | Required                                                                                                               |                |
| CHEMICAL PROPERTIES                                       |                                                                                     |                                                                                                                                                                                                                        |                                                                                                                        |                |
| Resistance to staining                                    |  | ISO 10545-14                                                                                                                                                                                                           | Minimum class 3                                                                                                        | Class 5        |
| Resistance to low concentrations of acids                 |  | ISO 10545-13                                                                                                                                                                                                           | Manufacturer to state classification                                                                                   | Class GLA      |
| Resistance to low concentrations of alkalis               |  | ISO 10545-13                                                                                                                                                                                                           | Manufacturer to state classification                                                                                   | Class GLA      |
| Resistance to household chemicals and swimming pool salts |  | ISO 10545-13                                                                                                                                                                                                           | Minimum GB                                                                                                             | GA             |
| APPLICATIONS                                              |  | Recommend residential or low-traffic commercial floor covering areas (indoor) suitable for normal footwear. Ex-Office areas, except entrances, Kitchens, and laboratories, which do not require strong acid resistance |                                                                                                                        |                |